



TASKI®

Plaza® Plus



F2

Sealer

Description

TASKI® Plaza® Plus is a floor sealer that is resistant to highly alkaline surfaces making it suitable for most terrazzo floors and porous concrete floors. Top coat Plaza Plus with a Diversey finish to provide a superior depth of gloss.

Excellent performance

- Superior adhesion to terrazzo and concrete floors that are high in alkalinity.
- Fast drying time.
- Superior clarity and depth of gloss.
- Excellent durability and levelling.
- Excellent adhesion to floor finishes.

Versatile

- One-product solution for non-resilient and resilient surfaces, including terrazzo, marble, stone and concrete floors, granite, quarry tile, brick, unglazed ceramic as well as worn vinyl and vinyl composite.
- Excellent levelling and brilliant gloss that can withstand high traffic loads.

Designed for

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





TASKI®

Plaza® Plus



F2

Directions for use

Application:

1. Strip old coatings using a Diversey stripper according to label directions. Rinse with clean water. Floors must be clean, dry and free of residue before sealer is applied.

2a. Used as a sealer only: Apply 3 or more uniform coats of TASKI® Plaza® Plus using a clean finish mop. Allow at least 45 minutes dry time between coats.

2b. Used as a sealer before top coating with a finish: Apply 2 uniform coats of TASKI® Plaza® Plus using a clean finish mop. Allow each coat to dry thoroughly at least for 45 minutes depending on drying conditions. Top coat with a Diversey finish according to label directions.

Do not apply more than 4 coats within a 24-hour period.

Make sure previous coats are completely dry before applying another coat.

Temperature, humidity and ventilation may affect drying time

Maintenance:

1. Dust mop or sweep to remove dust and dirt.
2. Clean floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to label directions.
3. Maintain the Diversey finish gloss using periodic recoating, spray buffing or burnishing according to Diversey finish directions.
4. Wash out all equipment before storage.

Consult your Diversey Representative for additional information.

Technical data			
Appearance	Milky white liquid	Specific Gravity (20°C)	1.03
Odour	Product specific	pH (concentrate)	9.0
Coverage	40 – 60m ² per litre	Dry time	Approx. 60 minutes
Dilution	Neat		

The above data is typical of normal production and should not be taken as a specification.

Product	Pack size	SKU Code	Availability
TASKI® Plaza® Plus	2 x 5L	5623653	AU & NZ

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.

Store in original container. Avoid extremes of temperature and humidity.

Product compatibility

Under recommended conditions of use, TASKI® Plaza Plus is suitable on most resilient and non-resilient (porous) floors. Not suitable on linoleum and rubber floors.

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com.

© 2018 Diversey, Inc. All Rights Reserved. Legal disclaimer: The associated products or services are manufactured by or otherwise emanate from Diversey Companies and their subsidiaries and not from Sealed Air.