



TASKI®

Snapback



F3

Maintainer

Description

TASKI® Snapback is a spray buffing product that enhances the appearance of worn water based floor finishes. TASKI® Snapback produces a brilliant gloss whilst removing scuffs, scratches and dirt in swing or cord electric buff floorcare systems.

Features

- Cleans and shines.
- Removes scuffs, scratches and dirt.
- Can be used as a spray buff, as a buff restorer/cleaner.
- Does not build up over time.
- Can be used through an autoscrubber, mopped-on or in a trigger spray bottle.
- Maintenance speed: 500 -1500rpm.

Benefits

- Improves gloss whilst removing scuffs, surface scratches, ground in dirt and black heel marks.
- Snapback cleans and shines saving time and money by doing two jobs in one.
- Improves appearance of worn floors.

Application areas

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





TASKI®

Snapback



F3

Maintainer

Directions for use

Spray Buff

1. Dust mop or sweep to remove any dust or dirt.
2. Clean floor with Diversey cleaner diluted in cold water according to label directions. Allow floor to dry completely before spray buffing.
3. Spray a light mist of TASKI® Snapback diluted 200ml per litre (1:4) with cold water unto the floor. Do not over wet the floor.
4. Buff the floor using an approved pad with a low speed swing machine.

Mop & Bucket

1. Dust mop or sweep floor to remove dust or dirt.
2. Dilute 15ml per litre (1:60) of TASKI® Snapback to cold water. Mop floor clean with TASKI® Snapback. Pick up soil and excess cleaner with a tightly wrung-out cleaning mop. Do not rinse floor after cleaning.
3. Allow floor to dry completely.
4. For best appearance burnish the floor with a high speed cord electric machine.

Coverage: 1000–1500 m² per litre.

Maintenance Speed: 500–1500 rpm.

In New Zealand: MPI Approved C 25 (All animal product except dairy).

Technical data			
Appearance	Clear off-white liquid	Odour	Lemon fresh
pH (concentrate)	12.7	pH (1:5)	12.5
Coverage	1000 – 1500 m ² per litre	Specific Gravity (20°C)	1.04
Maintenance speed	500 – 1500 rpm	Dilution	1:4 (Spray buffing) 1:60 (Mop method)

The above data is typical of normal production and should not be taken as a specification.

Product	Pack size	SKU Code	Availability
TASKI® Snapback	2 x 5L	5687606	AU & NZ

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity.

Product compatibility

Under recommended conditions of use, TASKI® Snapback is suitable on most floor types.

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com.